

MATERIAL SAFETY DATA SHEET

Creation Date : 07 April, 2020

Last Update : 09 Sep, 2025

Page 1 of 5

Product name : Ni-MH 1600MAH 9.6V

The batteries referenced herein are exempt articles and are not subject to the OSHA Hazard Communication Standard requirement. This safety data sheet is provided as a service to our customers.

1. COMPOSITION / INFORMATION ON INGREDIENTS

The Nickel Metal Hydride battery is hermetically sealed ; among its components, the following ones could potentially be hazardous upon release.

Product name: Ni-MH 1600MAH 9.6V

Hazardous components	CAS-No.	EC-No.	Weight %
Nickel hydroxide	12054-48-7	235-008-5	11-26%
Iron	7439-89-6	231-096-4	12-13%
Cobalt Oxide	11104-61-3	215-154-6	8-15%
Lithium hydroxide	1313-65-2	215-183-4	3-10%
Potassium hydroxide(liquid)	1310-58-3	215-181-3	<5

For the full text of the R phrases mentioned in this Section, see Section 15.

2. HAZARDS IDENTIFICATION

Classification	Carcinogenic Category 3 R40, sensitizing R42/43, Xn R20/22, C R35, N R50-53
Most important hazards	Limited evidence of a carcinogenic effect. Causes severe burns Harmful by inhalation and if swallowed. May cause sensitization by inhalation and skin contact. Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Further information	The Nickel Metal Hydride is a sealed battery which is not hazardous when used according to recommendations. Under normal conditions of use, the integrity of the battery casing and security vent are maintained, the ingredients are not expected to pose a significant risk to man or the environment. On some bad using conditions (high over-charge, inverse charge, external short circuit) and in case of a bad functioning, some electrolyte leakage can occur by the safety vent. In these cases, the risk is the caustic nature of electrolyte (potassium hydroxide). The classification above is based on the contents being considered as a preparation in accordance with Directive 1999/45/EC



Creation Date : 07 April, 2020

Last Update : 09 Sep, 2025

Product name: Ni-MH 1600MAH 9.6V

3. FIRST AID MEASURES

General advice

Show this safety data sheet to the doctor in attendance.

The information below refers to exposure to the ingredients.

Inhalation

Immediate medical attention is required. Move to fresh air. If symptoms persist, call a physician.

Skin contact

Immediate medical attention is required. Wash off immediately with plenty of water for at least 15 minutes.

Remove and wash contaminated clothing before re-use. If skin irritation persists, call a physician.

Eye contact

Immediate medical attention is required.

Remove contact lenses. Rinse immediately with plenty of water for at least 15 minutes.

Ingestion

Immediate medical attention is required. Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Do not induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Centre immediately.

4. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Dry powder, carbon dioxide (CO₂), sand.

Extinguishing media which must not be used for safety reasons

Water, water spray.

Specific hazards

Risk of receptacle bursting.

Special protective equipment for firefighters

In the event of fire, wear self contained breathing apparatus. Wear personal protective equipment.

Hazardous decomposition products

Nickel and cobalt compounds.

5. ACCIDENTAL RELEASE MEASURES

The information below refers to exposure to the ingredients.

Personal precautions

Use personal protective equipment.

Avoid contact with skin and eyes.

Environmental precautions

Prevent further leakage or spillage if safe to do so.

Do not allow material to contaminate ground water system.

Methods for cleaning up

Pick up and transfer to properly labelled containers.

Dispose of in accordance with local regulations.

Creation Date : 07 April, 2020

Last Update : 09 Sep, 2025

Product name : Ni-MH 1600MAH 9.6V

7. HANDLING AND STORAGE

Handling

Technical measures/Precautions

No special technical protective measures required.

Do not obstruct safety vent by soldering or welding tabs on the positive top.

Safe handling advice

Avoid contact with skin and eyes.

Use personal protective equipment.

Storage

Technical measures/Storage conditions

Keep in a dry, cool and well-ventilated place, preferably in the temperature range of +5 to +25!aC
at 65%(+5%)
relative humidity.

Keep away from heat and sources of ignition.

Ensure battery terminals are protected during storage.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational exposure controls

Engineering measures

Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Not required under normal use.

The information below refers to exposure to the ingredients.

Respiratory protection

Wear a positive-pressure supplied-air respirator with full facepiece.

Hand protection

Neoprene gloves (EN374).

Eye protection

Safety glasses with side-shields conforming to EN166.

Skin and body protection

Boots, apron, protective suit.

Hygiene measures

General industrial hygiene practice.

Environmental exposure controls

The information below refers to exposure to the ingredients

Prevent product from entering drains.

Do not allow material to contaminate ground water system.

9. PHYSICAL AND CHEMICAL PROPERTIES

General Information

Form	battery (sealed unit)	Colour	not applicable	Odour	odourless
------	-----------------------	--------	----------------	-------	-----------

Important Health Safety and Environmental Information

not applicable

Creation Date : 07 April, 2020

Last Update : 09 Sep, 2025

Product name : VB Ni-MH 1600MAH 9.6V

10. STABILITY AND REACTIVITY

Stability

Stable under normal conditions.

Hazardous polymerisation

Hazardous polymerisation does not occur.

Conditions to avoid

Keep away from heat and sources of ignition.

Materials to avoid

Exposure to moisture.

Hazardous decomposition products

Nickel and cobalt compounds.

11. TOXICOLOGICAL INFORMATION

The information below refers to exposure to the ingredients

Local effects

Causes severe burns. Risk of serious damage to eyes. Harmful by inhalation and if swallowed.

Long term toxicity

No data available. Avoid repeated exposure.

Specific effects

May cause sensitization by inhalation and skin contact.

Limited evidence of a carcinogenic effect.

12. ECOLOGICAL INFORMATION

If used as directed, and if the integrity of the battery casing and security vent are maintained, the ingredients are not expected to pose a significant risk to the environment.

Mobility

No data available.

Persistence and degradability

No data available.

Ecotoxicity effects

The information below refers to exposure to the ingredients

Nickel hydroxide: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products

Dispose of in accordance with local regulations. It must undergo special treatment, e.g. at suitable disposal site to comply with local regulations. Should not be released into the environment.

Contaminated packaging

Not applicable.

Further information

EWC waste disposal No: 200133 - batteries and accumulators included in 16 06 01, 16 06 02 or 16 06 03 and

unsorted batteries and accumulators containing these batteries

Never incinerate Ni-MH batteries.

Never dispose Ni-MH batteries as landfill.

Nickel-Metal Hydride batteries - which in some countries may not be subject to collection & recycling

and/or disposal requirements "Cdo however contain recyclable materials and GREPOW recommends

proper recycling of these batteries whenever possible.

Creation Date : 07 April, 2020

Last Update : 09 Sep, 2025

Product name : Ni-MH 1600MAH 9.6V

14. TRANSPORT INFORMATION

IATA, IMDG, Model Regulation	N/A
Proper Shipping Name/Description	
IATA, IMDG, Model Regulation	N/A
Class or Div. (Sub Hazard)	
IATA, IMDG, Model Regulation	Not Subjected for transport of dangerous goods
Packing Group	
IATA, IMDG, Model Regulation	N/A
Hazard Label	
IATA, IMDG, Model Regulation	N/A
Environmental hazards	
Marine pollutant:	No
Special precautions for user	No information available.

The Ni-MH 1600MAH 9.6V rechargeable Ni-MH batteries are considered to be "dry cell" batteries and are not subject to

dangerous goods regulation for the purpose of transportation by the U.S. Department of Transportation (DOT),

the International Civil Aviation Organization (ICAO), the International Air Transport Association (IATA) or the

International Maritime Dangerous Goods regulations (IMDG). The only DOT requirement for shipping Nickel

Metal Hydride batteries is Special Provision 130 which states: "Batteries, dry are not subject to the requirements

of this subchapter only when they are offered for transportation in a manner that prevents the dangerous

evolution of heat (for example, by the effective insulation of exposed terminals)." IATA requires that batteries

being transported by air must be protected from short-circuiting and protected from movement that could lead

to short-circuiting. The International Maritime Dangerous Goods Code (IMDG) regulate them for ocean

transportation under Special provision 304 which says "Batteries, dry, containing corrosive electrolyte which will

not flow out of the battery if the battery case is cracked are not subject to the provisions of this Code provided

the batteries are securely packed and protected against short-circuits. Examples of such batteries are: alkali-manganese, zinc carbon, nickel metal hydride and nickel-cadmium batteries.!

We hereby certify that the consignment is not classified as dangerous goods under the current edition of the IATA

Dangerous Goods Regulations.

15. REGULATORY INFORMATION

Symbol C Corrosive

N Dangerous for the environment

Text of R phrases mentioned in Section 2

R22 - Harmful if swallowed.

R20/22 - Harmful by inhalation and if swallowed.

R35 - Causes severe burns

R40 - Limited evidence of a carcinogenic effect.

R42/43 - May cause sensitization by inhalation and skin contact.

R43 - May cause sensitization by skin contact.

R50/53 - Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

16. OTHER INFORMATION

S Phrases S 1/2 - Keep locked up and out of the reach of children.

S36/37/39 - Wear suitable protective clothing, gloves and eye/face protection.

S45 - In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

S60 - This material and its container must be disposed of as hazardous waste.

S61 - Avoid release to the environment. Refer to special instructions/safety data sheets.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

