

扫二维码  
关注谱尼测试

Pony Testing International Group

Report No.: MOIURCSJ47497716

# MSDS Report

Sample Name  
& Model

Nickel Metal Hydride Battery SC1800mAh 7.2V



No.: MOIURCSJ47497716  
Code: yeqf3b



北京实验室: (010)83055000

上海实验室: (021)64851999 长春实验室: (0431)85150908

青岛实验室: (0532)88706866 大连实验室: (0411)87336618

深圳实验室: (0755)26050909 哈尔滨实验室: (0451)58627755

天津实验室: (022)27360730 郑州实验室: (0371)69350670

苏州实验室: (0512)62997900 新疆实验室: (0991)6684186

石家庄实验室: (0311)85376660

西安实验室: (029)89608785

呼和浩特实验室: (0471)3450025

杭州实验室: (0571)85806807

宁波实验室: (0574)87977185

武汉实验室: (027)83997127

合肥实验室: (0551)63843474

广州实验室: (020)89224310

厦门实验室: (0592)5568048

成都实验室: (028)87702708



Pony Testing International Group

Report No.: MOIURCSJ47497716 Date: 2021-01-04 Page 1 of 10

# Material Safety Data Sheet

Reference to ST/SG/AC.10/30/Rev.8 (GHS)

## Section 1 - Chemical Product and Company Identification

### Chemical Product Identification

**Sample Name:** Nickel Metal Hydride Battery

**Sample Model:** SC1800mAh 7.2V

**Recommended Uses:** N/A

**Restrictions on Use:** N/A

## Section 2 - Hazards Identification

**Emergency overview:** This product is a battery. Intended use of the product should not result in exposure to the chemical substance. In case of rupture the below hazards exist.

### Classification according to GHS

Acute toxicity, oral (4)

Acute toxicity, inhalation: Dusts and mists (4)

Skin corrosion/irritation (1A, 1B, 1C)

Sensitisation, respiratory (1, 1A, 1B)

Sensitisation, skin (1, 1A, 1B)

Carcinogenicity (2)

Specific target organ toxicity, single exposure; Respiratory tract irritation (3)

Specific target organ toxicity, repeated exposure (2)

Hazardous to the aquatic environment, long-term hazard (1)

### Label elements

**Hazard pictogram(s):**

**Signal word:**

Danger





Pony Testing International Group

Report No.: MOIURCSJ47497716 Date: 2021-01-04 Page 2 of 10

**Hazard statement(s):**

H302 Harmful if swallowed

H332 Harmful if inhaled

H314 Causes severe skin burns and eye damage

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled

H317 May cause an allergic skin reaction

H351 Suspected of causing cancer

H335 May cause respiratory irritation

H373 May cause damage to organs through prolonged or repeated exposure

H410 Very toxic to aquatic life with long lasting effects

**Precautionary statement(s):**
**Prevention:**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dusts or mists.

P264 Wash skin and clothing thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves, protective clothing, eye protection, face protection.

**Response:**

P330 Rinse mouth.

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER.

P301 + P330 + P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P363 Wash contaminated clothing before reuse.

P321 Specific treatment(See additional emergency instructions).

P391 Collect spillage.

**Storage**

P405 Store locked up.

**Disposal:**

P501 Send contents to approved waste treatment plants.

**Other hazards**
**Physical and chemical hazards:** See Section 10





Pony Testing International Group

Report No.: MOIURCSJ47497716 Date: 2021-01-04 Page 3 of 10

**Human health hazards:** See Section 11**Environmental hazards:** See Section 12

### Section 3 – Composition/Information on Ingredients

**Chemical characterization:** Mixture

Chemical Composition	CAS No.	EC#	Weight (%)
Nickel Hydroxide	12054-48-7	235-008-5	11~26
Iron	7439-89-6	231-096-4	12~13
Cobalt oxide	11104-61-3	234-334-5	8~15
Lithium Hydroxide	1310-65-2	215-183-4	3~10
Potassium hydroxide	1310-58-3	215-181-3	<5
Sodium hydroxide	1310-73-2	215-185-5	<2
Nylon	---	---	11~26
Others	---	---	<1

### Section 4 - First Aid Measures

**Description of first aid measures****General information** No special measures required.**After eye contact**

Flush eyes with plenty of water for several minutes while holding eyelids open. Get medical attention if irritation persists.

**After skin contact**

Remove contaminated clothing and shoes. Immediately wash with water and soap and rinse thoroughly. Wash clothing and shoes before reuse. If irritation occurs, get medical attention.

**After inhalation**

Remove victim to fresh area. Administer artificial respiration if breathing is difficult. Seek medical attention.

**After swallowing**

Do not induce vomiting. Get medical attention.

**Personal protective equipment for first-aid responders:** No data available.**Most important symptoms/effects, acute and delayed:** No data available.**Indication of immediate medical attention and special treatment needed:** Treat symptomatically.





## Section 5 - Fire Fighting Measures

### Suitable extinguishing media:

Use extinguishing agent suitable for local conditions and the surrounding environment. Such as dry powder, CO<sub>2</sub>.

### Unsuitable extinguishing media:

No data available.

### Specific Hazards arising from the chemical:

Special hazards arising from the substance or mixture

Battery may burst and release hazardous decomposition products when exposed to a fire situation.

Some may burn but none ignite readily. Containers may explode when heated. Some may be transported hot.

### Specific protective actions for fire-fighters:

Protective equipment: Wear self-contained respirator. Wear fully protective impervious suit.

## Section 6 - Accidental Release Measures

### Personal precautions:

Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation

### Protective equipment:

No data available.

### Emergency procedures:

Remove ignition sources, evacuate area. Sweep up using a method that does not generate dust.

Collect as much of the spilled material as possible, placed the spilled material into a suitable disposal container. Keep spilled material out of sewers, ditches and bodies of water.

### Environmental precautions:

Do not allow material to be released to the environment without proper governmental permits.

### Methods and materials for containment and cleaning up:

For all waste handling must refer to United Nations, National and Local Regulations for disposal.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## Section 7 - Handling and Storage

### Precautions for safe handling:

Avoid short circuiting the battery. Avoid mechanical damage of the battery. Do not open or disassemble. Batteries may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity. Avoid all personal contact, including





Pony Testing International Group

Report No.: MOIURCSJ47497716 Date: 2021-01-04 Page 5 of 10

inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps.

**Conditions for safe storage, including any incompatibilities:**

Store in a cool, dry, well-ventilated place. Keep away from heat, avoiding the long time of sunlight.

## Section 8 - Exposure Controls/Personal Protection

### Control parameters

CAS No.	ACGIH	NIOSH	OSHA
12054-48-7	N/A	N/A	N/A
7439-89-6	N/A	N/A	N/A
11104-61-3	N/A	N/A	N/A
1310-65-2	N/A	N/A	N/A
1310-58-3	TLV-Peak 2mg/m <sup>3</sup>	REL-Peak 2mg/m <sup>3</sup>	N/A
1310-73-2	N/A	N/A	PEL-TWA 2mg/m <sup>3</sup>

### Appropriate engineering controls:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Remove all soiled and contaminated clothing immediately.

Wash hands before breaks and at the end of work.

### Personal Protective Equipment:

**Respiratory protection:** Wear suitable protective mask. For a large large number of battery leakages, wear chemical protective clothing, including self-contained breathing apparatus.

**Hand Protection:** Wear appropriate protective gloves to reduce skin contact.

**Eye Protection:** Wear safety goggles or eye protection combined with respiratory protection.

**Skin and Body Protection:** Working environment required, wear suitable protective clothing to minimize contact with skin. The type of protective equipment must be according to the concentration and the content of certain hazardous substances in the workplace.

## Section 9 - Physical and Chemical Properties

### Information on basic physical and chemical properties

**Colour:** Green.

**Physical State:** Prismatic.

**Odour:** Not available.





Pony Testing International Group

Report No.: MOIURCSJ47497716 Date: 2021-01-04 Page 6 of 10

Odour threshold:	Not available.
pH:	Not available.
Melting point/freezing point:	Not available.
Initial boiling point and boiling range:	Not available.
Flash Point:	Not available.
Evaporation rate:	Not available.
Flammability (solid, gas):	Not available.
Explosion Limits (vol% in air):	Not available.
Vapour pressure, kPa at 20°C:	Not available.
Vapor density:	Not available.
Density/Relative density (water = 1):	Not available.
Solubility(ies):	Not available.
Partition coefficient: n-octanol/water:	Not available.
Auto-ignition temperature:	Not available.
Decomposition temperature:	Not available.
Viscosity:	Not available.
Other information:	
Voltage	7.2V
Electric capacity	1800mAh

## Section 10 - Stability and Reactivity

**Reactivity:** No data available.

**Chemical stability:** Stable.

**Possibility of hazardous reactions:** No data available.

**Conditions to Avoid:** Flames, sparks, and other sources of ignition, incompatible materials.

**Incompatible materials:** Oxidizing agents, acid base.

**Hazardous decomposition products:** Carbon monoxide, carbon dioxide.

## Section 11 - Toxicological Information

**Acute Toxicity:**

CAS No.	LC50/LD50
12054-48-7	LD50 Rat (oral): 1600mg/kg LC50 Rat (Inhalation: Dusts and mists): 1200mg/m <sup>3</sup>
7439-89-6	No data available.
11104-61-3	No data available.





Pony Testing International Group

Report No.: MOIURCSJ47497716 Date: 2021-01-04 Page 7 of 10

1310-65-2	LD50 Rat (oral): 210mg/kg; LC50 Rat (Inhalation: Dusts and mists): 0.96mg/L
1310-58-3	LD50 Rat (oral): 284mg/kg
1310-73-2	LD50 Rat(oral): 140~340mg/kg

**Skin corrosion/irritation:** No data available.**Serious eye damage/irritation:** No data available.**Respiratory or Skin sensitization:** No data available.**Germ Cell mutagenicity:** No data available.**Carcinogenicity:** No data available.**Reproductive toxicity:** No data available.**Specific target organ toxicity-Single exposure:** No data available.**Specific target organ toxicity-Repeated exposure:** No data available.**Aspiration hazard:** No data available.**Information on the likely routes of exposure:** No data available.**Eye:** No data available.**Skin:** No data available.**Ingestion:** No data available.**Inhalation:** No data available.

## Section 12 - Ecological Information

**Ecological Toxicity:** No data available.**Persistence and degradability:** No data available.**Bioaccumulative Potential:** No data available.**Mobility in Soil:** No data available.**Other adverse effects:** No data available.

## Section 13 - Disposal Considerations

**Disposal methods:****Recommendation:**

Consult state, local or national regulations to ensure proper disposal.

**Uncleaned packaging****Recommendation:** Disposal must be made according to official regulations.

## Section 14 - Transport Information





Pony Testing International Group

Report No.: MOIURCSJ47497716 Date: 2021-01-04 Page 8 of 10

<b>UN or ID Number</b>	
<b>IATA</b>	N/A
<b>IMDG</b>	UN3496
<b>Model Regulation</b>	N/A
<b>Proper Shipping Name/Description</b>	
<b>IATA</b>	N/A
<b>IMDG</b>	BATTERIES, NICKEL-METAL HYDRIDE
<b>Model Regulation</b>	N/A
<b>Class or Div. (Sub Hazard)</b>	
<b>IATA</b>	Not Subjected for transport of dangerous goods
<b>IMDG</b>	9
<b>Model Regulation</b>	Not Subjected for transport of dangerous goods
<b>Packing Group</b>	
<b>IATA</b>	N/A
<b>IMDG</b>	N/A
<b>Model Regulation</b>	N/A
<b>Hazard Label</b>	
<b>IATA</b>	N/A
<b>IMDG</b>	
<b>Model Regulation</b>	N/A
<b>Environmental hazards</b>	
<b>Marine pollutant:</b>	No
<b>Special precautions for user</b>	No information available.

**Transport information: Nickel Metal Hydride Battery SC1800mAh 7.2V is exempt from dangerous goods.** It is considered non-dangerous goods by the International Civil Aviation Organization (ICAO), the International Air Transport Association (IATA) DGR 62<sup>nd</sup>, IATA Special Provisions A199, International Maritime Dangerous Goods Regulations (IMDG) (39-18), IMDG Special Provisions 963, or the 《Recommendations on the Transport of Dangerous Goods Model Regulations》 (21<sup>st</sup>).

**S.P.A199** The UN number UN 3496 is only applicable in sea transport. Nickel-metal hydride battery or nickel-metal hydride battery-powered devices, equipment or vehicles having the potential of a dangerous evolution of heat are not subject to these Regulations provided they are prepared for transport so as to prevent:

- (a) a short-circuit (e.g. in the case of batteries, by the effective insulation of exposed terminals; or, in the case of equipment, by disconnection of the battery and protection of exposed terminals); and
- (b) unintentional activation.





Pony Testing International Group

Report No.: MOIURCSJ47497716 Date: 2021-01-04 Page 9 of 10

The words "Not Restricted" and the Special Provision number must be included in the description of the substance on the Air Waybill as required by 8.2.6, when an Air Waybill is issued.

Separate batteries when shipping to prevent short-circuiting. They should be packed in strong packaging for support during transport.

**Transport Fashion:** By air, by sea, by railway, by road.

## Section 15 - Regulatory Information

**Safety, health and environmental regulations/legislation specific for the substance or mixture**

CAS No.	TSCA	IECSC	DSL/NDSL	EINECS/ ELINCS/ NLP
12054-48-7	Listed	Listed	Listed DSL	Listed
7439-89-6	Listed	Listed	Listed DSL	Listed
11104-61-3	Listed	Listed	Listed DSL	Listed
1310-65-2	Listed	Listed	Listed DSL	Listed
1310-58-3	Listed	Listed	Listed DSL	Listed
1310-73-2	Listed	Listed	Listed DSL	Listed

## Section 16 - Other Information

Issue Date: 2021-01-04

Issue Department: Technical department

Modification record:

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Other Information:

CAS: (Chemical Abstracts Service);

EC: (European Commission);

ACGIH: (American Conference of Governmental Industrial Hygienists);

NIOSH: (US National Institute for Occupational Safety and Health);



Hotline 400-819-5688  
 Pony Testing Group Shenzhen Co., Ltd.  
 Address: 3/F of Building 2, Building 1, Xinhaocheng Industrial Park, Yonghe Road, Qiaotou Community, Baoan District, Shenzhen, Guangdong, China  
 Phone: 0755-26050909  
 www.ponytest.com

北京实验室: (010) 83055000  
 上海实验室: (021) 64851999  
 青岛实验室: (0532) 88706866  
 深圳实验室: (0755) 26050909  
 天津实验室: (022) 23607888  
 苏州实验室: (0512) 62997900  
 武汉实验室: (027) 83997127  
 武汉车附所: (027) 82318175  
 长春实验室: (0431) 80530198  
 大连实验室: (0411) 87336618  
 哈尔滨实验室: (0451) 58627755  
 郑州实验室: (0371) 69350670  
 新疆实验室: (0991) 6684186  
 石家庄实验室: (0311) 85376660  
 西安实验室: (029) 89608785  
 杭州实验室: (0571) 85806807  
 宁波实验室: (0574) 87977185  
 呼和浩特实验室: (0471) 3450025  
 太原实验室: (0351) 7555722  
 南宁实验室: (0771) 5554165  
 合肥实验室: (0551) 63843474  
 广州实验室: (020) 89224310  
 厦门实验室: (0592) 5568048  
 成都实验室: (028) 87702708





Pony Testing International Group

OSHA: (US Occupational Safety and Health);  
 TLV: (Threshold Limit Value)  
 TWA: (Time Weighted Average);  
 STEL: (Short Term Exposure Limit);  
 PEL: (Permissible Exposure Level);  
 REL: (Recommended Exposure Limit);  
 PC-STEL: (Permissible concentration-short time exposure limit);  
 PC-TWA: (Permissible concentration-time weighted average);  
 LC50: (Lethal concentration, 50 percent kill);  
 LD50: (Lethal dose, 50 percent kill);  
 IARC: (International Agency for Research on Cancer);  
 EC50: (Median effective concentration);  
 BCF: (Bioconcentration Factor);  
 BOD: (Biochemical oxygen demand);  
 NOEC: (No observed effect concentration);  
 NTP: (US National Toxicology Program);  
 RTECS: (Registry of Toxic Effects of Chemical Substances);  
 IATA: (International Air Transport Association);  
 IMDG: (International Maritime Dangerous Goods);  
 TDG: (Recommendations on the TRANSPORT OF DANGEROUS GOODS Model Regulations);  
 TOC: (Total Organic Carbon);  
 TSCA: (Toxic Substances Control Act of USA);  
 DSL: (the Domestic Substances List of Canada);  
 NDSL: (the Non-domestic Substances List of Canada)

\*\*\*End of report\*\*\*